

FP14KC-X

Four Post, Commercial Service Lift (Closed Front / Cable Pull) **14,000 lbs. Capacity**

The iDEAL FP14KC-X 14,000 lb. Four Post Commercial Service Lift is a high-performance closed front, cable pull vehicle lift designed for Cars, SUVs, Vans & Trucks. The FP14KC-X Service Lift includes the latest in design & safety features including, narrow & wide runway mount positions, extended rise height for greater undercarriage vehicle access, concealed hydraulic / mechanical cable lift system with slack cable safety devices and durable pulley & shaft design incorporating convenient grease fittings to extended life of the lift. Easy lift operation is provided with single point pneumatic lock release & high-quality DURO power unit, while providing additional safety & protection with self-chocking ramps and included wheel stops. The iDEAL FP14KC-X modular design provides the flexibility to extend the runways for servicing longer vehicles, while also providing the ability to convert into a high-quality Alignment Lift quickly & easily! The standard provided powder coat finish, 20" wide runways, adjustable lock stops for easy runway leveling and optional power unit mount positions complete the package for a premium, high quality service lift, all at an unmatched value!

Features

- 14,000 LBS CAPACITY
- HIGH PERFORMANCE COMMERCIAL SERVICE LIFT
- DURABLE, HIGH QUALITY CABLE LIFT SYSTEM
- EXTENDED RISE HEIGHT
- 182.5" MAX WHEELBASE
- 18 LOCKING HEIGHT POSITIONS
- 20" WIDE RUNWAYS
- NARROW & WIDE RUNWAY MOUNTING POSITIONS
- SINGLE POINT PNEUMATIC LOCK RELEASE
- FULLY ADJUSTABLE LOCK STOPS FOR EASY LEVELING
- SLACK CABLE SAFETY DEVICES
- SELF-CHOCKING APPROACH RAMPS W/ NYLON ROLLERS
- WHEEL CHOCKS (1PR)
- DURABLE POWDER COAT FINISH

Specifications

Lift Model	FP14KC-X
Capacity	14,000 lbs.
Overall Length w/ Ramp	252-1/2"
Overall Width (Without Power Unit)	131-7/8"
Overall Width (With Power Unit)	142"
Overall Height	92-1/2"
Max Rise Height	77-1/2"
Min Height	7-7/8"
Width Between Posts	116-1/4"
Length Between Posts	196"
Width Between Runways	43" or 46"
Width of Runways	20"
Max Wheelbase	182-1/2"
Ramp Length	44"
Max. Clearance Under Runway	69-5/8"
Drive-Thru Clearance	96"
Base Plate	10-1/2" x 9"
Power Requirement	220V - 20 Amp - 1PH
Ship Weight	2,690 lbs.
Min Bay Size	16' x 25'



Exclusive Features!!

- ABLE TO EXTEND RUNWAYS 24" W/ RUNWAY EXTENSION KIT
- EASIER INSTALL & SERVICE AS NO NEED TO REMOVE CROSSRAIL PULLEYS FOR CABLE ACCESS & REPLACEMENT
- GREASE ZERKS APPLIED FOR ALL CABLE PULLEYS & SHAFT ASSEMBLIES
- HIGH-QUALITY DURO POWER UNIT W/ UL LISTED MOTOR & SWITCH COMPONENTS
- QUICKLY CONVERTS TO ALIGNMENT LIFT W/ ADDITION OF 'BOLT-ON' ALIGNMENT KIT

Premium Products at Affordable Prices!!

FP14KC-X

More Features, More Value!!

HIGH PERFORMANCE, COMMERCIAL SERVICE LIFT
14,000 lb. CAPACITY / 182.5" MAX WHEELBASE




FP14KC-X Optional Accessories



RAJ-7K-H
IDEAL, 7K ROLLING AIR JACK - (HIGH MOUNT)

- 7,000 LBS. CAPACITY
- HIGH MOUNT DESIGN FOR LOW POSITION JACK RAILS
- ADJUSTABLE HEIGHT ROLLER BODY ASSEMBLIES
- DUAL 'SPRING LOADED' ROLLER BODY OPERATION
- SMOOTH 'ON-RAIL' ROLLING W/ ROLLER BEARING WHEELS
- TELESCOPING & LOCKING SUPPORT ARMS
- AIR / HYDRAULIC OPERATION
- PROTECTIVE SKIRTS
- TWO LOCKING HEIGHT POSITIONS
- RUBBER HEIGHT ADAPTERS (SET OF 2EA)



FP14KCX-24EXTKIT
IDEAL, 24" RUNWAY EXTENSION KIT (FP14KC-X)

- SET OF TWO
- DESIGNED FOR USE W/ FP14KC-X & FP14KAC-X LIFT MODELS
- LENGTHENS RUNWAYS BY 24" FOR EXTENDED WHEELBASE REQUIREMENTS
- EXTENDS FP14KC-X LIFT TO 206" MAX SERVICE WHEELBASE
- EXTENDS FP14KAC-X LIFT TO 190.7" MAX ALIGNMENT WHEELBASE (2 WHEEL) (* 24" EXT. ALIGNMENT SPACER KIT REQUIRED TO EXTEND FP14KAC-X ALIGNMENT RUNWAYS)
- EASY 'BOLT-ON' DESIGN
- INCLUDES ALL MOUNTING HARDWARE
- DURABLE POWDER COAT FINISH



FP14KCX-ALK
IDEAL, AIR LINE KIT W/ FRL (FP14KC-X)

- DESIGNED FOR USE W/ FP14KC-X LIFT & RAJ-7K MODELS
- INCLUDES COILED HOSES, AIR TUBING, AIR FITTINGS & QUICK DISCONNECT FITTINGS TO RAJs.
- INCLUDES FRL (FILTER, REGULATOR & LUBRICATOR)
- QUICK RETRO-FIT INSTALLATION DESIGN
- INCLUDES ALL MOUNTING HARDWARE



FP14KCX-ALIGNKIT
IDEAL, ALIGNMENT KIT 'BOLT-ON' (FP14KC-X)

- DESIGNED TO EASILY CONVERT FP14KC-X SERVICE LIFT TO ALIGNMENT LIFT
- ALIGNMENT KIT QUICKLY 'BOLTS' TO PRE-DRILLED HOLES IN FP14KC-X RUNWAYS
- PROVIDES ALIGNMENT MAX WHEELBASES OF 166.7" (2 WHEEL) & 157" (4 WHEEL)
- INCLUDES REAR SLIP PLATES, CENTER PANELS, TURNABLE SADDLES & CUTOUTS
- PROVIDES LEVEL SURFACE FROM TURNABLE CUTOUTS TO REAR SLIP PLATES
- NYLON SADDLE PADS FOR EASY & PROTECTIVE TURNABLE POSITIONING
- TURNABLE SPACER COVERS & EXTENDED HEIGHT WHEEL STOPS
- INCLUDES ALL MOUNTING HARDWARE
- DURABLE POWDER COAT FINISH
- TURNABLES NOT INCLUDED