HOLLSTEIN Balancer

We offer the best value in the industry

High performance



Features:

- · Self-calibrating
- Weight storage
- Pegs for accessories
- 8" long shaft with 36mm diameter
- Three auto STD centering cones
- ST,AL1 AL2,AL3, AL4 balancing methods
- Speed nut comes standard



Features:

- · Self calibrating
- · Self diagnosis
- Optimization program
- Static balancing
- alu-s balancing for light alloy rims
- Split function (hidden weights)
- Multiple operator program
- . Three centering cones
- · Weight storage
- · Pegs for accessories
- Hood, hammer, speed nut and caliper standard
- Optional motorcyle adapter is available



Optional: Light truck cone set -





Optional: motorcycle adapter kits –

Specifications	small	large
Cycle time	10 sec.	10 sec.
Method of data entry	keypad	keypad
Tire diameter	35"	39"
Tire width	1 %"-20"	1 1/1" - 20"
Rim diameter	10"-24"	10"-24"
Wheel weight	143 lbs.	150 lbs.
Accuracy	1 gram	1 gram
Power requirements	110 vac	110 vac

These are top performing balancers at an affordable price. They have all the features of the big guys. Standard features include: self-calibrating, dynamic, static and alloy capability, and a speed nut. The quick keypad data entry system makes tire balancing fast and efficient.